

56 GbE- and 8 10GbE-port Layer 3 full Gigabit modular managed Ethernet switches



reddot winner 2024



Features and Benefits

- 8 10GbE Ethernet ports
- Up to 56 1GbE ports or SFP slots
- HAST (High-availability Static Trunk) technology supports backbone reliability
- Onboard LCM display for at-a-glance status updates supports easy on-site maintenance and operation
- Dual power modules and 6+2 fan redundancy design for non-stop network operations
- Real-time system temperature monitoring to protect network and devices

Certifications



Introduction

The MRX-G4064 Series is designed to meet the high-performance, high-availability requirements of industrial video, voice, and data applications resulting from the growing convergence of information technology in industrial sites.

The modular design of the MRX-G4064 Series supports 8 10GbE ports built-in and up to 56 1GbE ports via modules, ideal for building large-scale industrial network applications. 10GbE ports significantly increase the network switching bandwidth, allowing for direct connections to 10GbE-enabled servers and moving data collection and analysis closer to the application site. Additionally, support for multi-port aggregation allows for higher bandwidth backbone, while also leaving room for future network growth.

In addition to accommodating larger numbers of field devices, MRX-G4064 Series reduces the delay of data transmission and enables the rapid transmission of large amounts of video, voice, and data on high-performance networks. This series is equipped with a redundant multi-fan cooling system and redundant isolated power supplies. It supports industrial high-efficiency Turbo Ring technology, as well as other network redundancy technologies such as ERPS (ITU-T G.8032) and RSTP/STP, which can enhance the reliability and availability of backbone networks in IT/OT convergence applications.

Additional Features and Benefits

- Flexible bandwidth/port combinations for effective bandwidth management and maximum reliability
- Command line interface (CLI) for quick management
- Out-of-band management (OOBM) port to ensure the availability of network management when in-band services are inaccessible
- System temperature control and power consumption management for non-stop operations
- Port mirroring (N:M) technology to support security monitoring and auditing
- Optimized for large burst transmissions of large-scale video surveillance to prevent frame loss
- IEEE1588v2 PTP (Precision Time Protocol) for network time synchronization
- Supports MXconfig and MXview One for industrial network management and visualization

Specifications

Ethernet Interface

1000/2500/10000BaseSFP Ports	8
1000BaseSFP Slots	8
Out-of-band Management (OOBM)	1 x 8-pin RJ45 1GbE Ethernet port (MGMT)

Module	<p>There are 3 module slots on the switch. Users can select different types of modules to insert into the switch. The modules that can be selected include 16-port modules with 1000BaseT(X) or 1000BaseSFP interfaces.</p> <p>Refer to Expansion Modules in the Accessories section for a full list of supported interface modules.</p>
Standards	<p>IEEE 802.1D-2004 for Spanning Tree Protocol IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1s for Multiple Spanning Tree Protocol IEEE 802.1w for Rapid Spanning Tree Protocol IEEE 802.1X for Authentication IEEE 802.3ab for 1000BaseT(X) IEEE 802.3ad for Port Trunk with LACP IEEE 802.3x for Flow Control IEEE 802.3z for 1000BaseSX/LX/LHX/ZX IEEE 802.3ae for 10 Gigabit Ethernet IEEE 802.3az for Energy-Efficient Ethernet ITU-T G.8032 Ethernet Ring Protection Switching</p>

Ethernet Software Features

Management	<p>IPv4 Flow control Back Pressure Flow Control DHCP Client ARP RARP LLDP Linkup Delay SMTP SNMP Trap SNMP Inform SNMPv1/v2c/v3 RMON TFTP SFTP HTTP HTTPS Telnet Syslog Private MIB Port Mirroring (SPAN, RSPAN)</p>
Filter	<p>GMRP GVRP GARP 802.1Q IGMP Snooping v1/v2/v3 IGMP Querier</p>
Redundancy Protocols	<p>STP RSTP Turbo Ring v2 Ring Coupling Multiple Dual-Homing Link Aggregation Network Loop Protection MSTP</p>
Routing Redundancy	<p>VRRP</p>
Security	<p>Broadcast storm protection Rate Limit Access control list Static port lock Sticky MAC HTTPS/SSL SSH RADIUS TACACS+ Login and password policy</p>

	Secure Boot
Time Management	SNTP IEEE 1588v2 PTP (hardware-based) NTP Server/Client NTP Authentication
Protocols	TCP/IP UDP ICMP ARP RARP TFTP DNS NTP Client DHCP Client 802.1X QoS HTTPS HTTP Telnet SMTP SNMPv1/v2c/v3 IPv4 RMON Syslog
Unicast Routing	OSPF Static Route
MIB	P-BRIDGE MIB Q-BRIDGE MIB IEEE8021-SPANNING-TREE-MIB IEEE8021-PAE-MIB IEEE8023-LAG-MIB LLDP-EXT-DOT1-MIB LLDP-EXT-DOT3-MIB SNMPv2-MIB RMON MIB Groups 1, 2, 3, 9

Switch Properties

MAC Table Size	32 K
Max. No. of VLANs	512
IGMP Groups	1500
Jumbo Frame Size	9.6 KB
Packet Buffer Size	6 MB
Priority Queues	8
VLAN ID Range	VID 1 to 4094

USB Interface

Storage Port	USB Type A
--------------	------------

MicroSD Interface

Storage Port	microSD card
--------------	--------------

Serial Interface

Console Port	RS-232 (RJ45)
--------------	---------------

Input/Output Interface

Alarm Contact Channels	1 relay output with current carrying capacity of 2 A @ 30 VDC
------------------------	---

Power Parameters

Input Voltage	100-240 VAC, 50-60 Hz or 230-240 VDC (for each power supply)
Operating Voltage	90-264 VAC, 47-63 Hz or 180-300 VDC (for each power supply)
Overload Current Protection	Supported
Reverse Polarity Protection	Supported
Input Current	Max. 1.236 A @ 110 VAC Max. 0.675 A @ 220 VAC Max. 0.74 A @ 180 VDC Max. 0.439 A @ 300 VDC
Power Consumption (Max.)	Max. 134.2 W @ 110 VAC Max. 132.3 W @ 220 VAC Max. 133.2 W @ 180 VDC Max. 131.8 W @ 300 VDC Note: These are the maximum power consumption ratings for the device with the maximum number of modules installed.
Power Module	2 x slots (2 x PWR-300-HVA-IF power modules included)

Physical Characteristics

IP Rating	IP30
Dimensions	440 x 88 x 420 mm (17.32 x 3.46 x 16.54 in)
Weight	12 kg (26 lb)
Fan Module	8 x slots (8 x XM-4000-FAN-R preinstalled)
Installation	Rack mounting
Interactive Interface	Onboard LCM display Push buttons for configuration

Environmental Limits

Operating Temperature	-10 to 60°C (-14 to 140°F)
Storage Temperature (package included)	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (non-condensing)


Standards and Certifications

Safety	UL 62368-1 UL 61010-2-201 IEC 62368-1
EMC	EN 55032/35 EN 61000-6-2/-6-4
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 35 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV IEC 61000-4-5 Surge: Power: 4 kV; Signal: 4 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF IEC 61000-4-11 Voltage Dips & Interruptions
Railway	EN 50121-4
Shock	IEC 60068-2-27

Vibration	IEC 60068-2-6
Package Drop Test	ISTA 1A
Package Vibration Test	ISTA 1A
MTBF	
Time	1,337,959 hrs
Standards	Telcordia (Bellcore), GB
Warranty	
Warranty Period	5 years
Details	See www.moxa.com/warranty
Package Contents	
Device	1 x MRX-G4064-L3-8XGS Series switch (eight XM-4000-FAN-R fan modules preinstalled)
Power Supply	2 x PWR-300-HVA-IF power modules
Installation Kit	2 x rack-mounting ear 2 x plastic IP30 dust cover for PWR power modules 8 x round stickers for module screws
Documentation	1 x quick installation guide 1 x warranty card
Note	This product requires additional modules (sold separately) and IEC 60320 C15 power cords to function.

Dimensions

Unit = mm (inch)



SFP-1GEZXC	SFP module with 1 1000BaseEZ port with LC connector for 110 km transmission, 0 to 60°C operating temperature
SFP-1GEZXC-120	SFP module with 1 1000BaseEZ port with LC connector for 120 km transmission, 0 to 60°C operating temperature
SFP-1GSXC-T	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, -40 to 85°C operating temperature
SFP-1GLSXC-T	SFP module with 1 1000BaseLS port with LC connector for 1km/2km transmission, -40 to 85°C operating temperature
SFP-1GLXC-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature
SFP-1GLHXC-T	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1GZXC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1GTXRJ45-T	SFP module with 1 1000BaseT port with RJ45 connector for 100 m transmission, -40 to 75°C operating temperature
SFP-10GSRLC-T	SFP+ module with 1 10GBase-SR port, LC connector for 33m/82m/300m/400m transmission, -40 to 85°C operating temperature
SFP-10GLRLC-T	SFP+ module with 1 10GBase-LR port, LC connector for 10 km transmission, -40 to 85°C operating temperature
SFP-10GERLC-T	SFP+ module with 1 10GBase-ER port, LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-10GZRLC-T	SFP+ module with 1 10GBase-ZR port, LC connector for 80 km transmission, -40 to 85°C operating temperature

Cables

CN20070	10-pin RJ45 to DB9 female serial cable
PWC-C15US-3B-183	C15 power cord with US plug, 1.83 m
PWC-C15CN-3B-183	C15 power cord with CN plug, 1.83 m
PWC-C15EU-3B-183	C15 power cord with EU plug, 1.83 m

Software

LIC-MXviewOne-NEW-XN-SR	MXview One node license with customizable node quantity (minimum 1 node)
-------------------------	--

Storage Kits

ABC-02-USB	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, 0 to 60°C operating temperature
ABC-02-USB-T	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, -40 to 75°C operating temperature
ABC-03-microSD-T	MicroSD-based configuration backup and restoration tool, firmware upgrades, and log file storage tool for managed Ethernet switches and WLAN products, -40 to 85°C operating temperature

© Moxa Inc. All rights reserved. Updated May 21, 2024.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.